



presented by



Technical Bulletin 17-1

Date: May 14, 2017

Subject: Rule Adjustments and Clarifications

Adjustments and clarifications are identified in **red** below.

Appendix A – Vehicle Lists

Touring Class

Honda	Civic	12 - 15	1228	17 X 8	245/620-17	K24Z6 motor; A throttle body restrictor of TBA must be installed; maximum 8200 rpm limit; allowed width – 1758mm; may use TSX brakes
Honda	Civic	12 - 15	1228	17 X 8	245/620-17	May use IMSA spec engine (K24Z6 short-block with K20 head); A throttle body restrictor of 52mm must be installed; maximum 8500 rpm limit; allowed width – 1758mm; may use TSX brakes
Honda	Civic	16 - 17	1228	17 X 8	245/620-17	Allowed width - TBA mm; Boost limit - TBA
Mazda	ND Global MX-5 Cup	16- 17	TBA	15x8	225/580-15	Allowed width – TBA mm; Rev limit - TBA



presented by



Super Touring Class

BMW	M235iR	14 -	TBA	18 X 10	265/660-18	Allowed width – TBA mm; Boost limit – stock map
Porsche	Cayman	09 -	1296	F+R – 17x9 OR F – 18x9 R – 18x10	F+R – 245/620-17 OR F – 245/645-18 R – 265/660-18	3.4 litre with limited prep allowed, maximum 7000 rpm limit, allowed width Front – TBA, Rear – TBA
Subaru	WRX	08 -	1319	17 X 9	245/620-17*	Limited eligibility for vehicle. 2.5 litre turbo, maximum boost limit allowed 15 psi; May use rigid steel inlet tube; Allowed width 68.7"/1745mm

GT Sport Class

BMW	M235iR	14 -	TBA	18 X 10	265/660-18	TBA
Honda	Civic	06 - 11	1159	17 X 9	245/620-17*	Limited eligibility for vehicle/motor combination. K24motor with Kraftwerks SC system
Porsche	Cayman GT4	TBA	TBA	F – 18x9 R – 18x10	F – 245/645-18 R – 265/660-18	TBA